

AF8750E/UV Note Counter



AF8750E/UV

Benefits

- ◇ The highly advanced, 'E' for 'Enhanced' Electronics, Series of Currency Counter has 'Fail Safe' operating controls to ensure full security through visual and audible alarms, so preventing double, half, or chain note feeding and inadvertent 'rogue' or 'stranger' bank notes being included in the count, thus providing dependable count accuracy.
- ◇ The original and often copied, integral, selectable (On/Off), automatic Dust Proof Cover™ that reduces airborne pollution, reduces operating noise level and eliminates possible losses through 'flying' currency.
- ◇ Special formulation feeding components that ensure extended operational life and assured performance when handling all types and condition of currency, from loose 'brick' to distressed 'street' quality.

Features

- ◇ Three selectable counting speeds.
- ◇ Pre-set and variable batch counting via 10-key 'long-life' Keypad.
- ◇ Large (4-digit) counting LED.
- ◇ Electronic 'last usage' memory system for Function Settings.
- ◇ Automatic or Manual Start mode.
- ◇ Batch Display (3-digit LED).
- ◇ UV Counterfeit Detection
- ◇ 'Off' plus 3, 4 & 5mm size detection (In the narrow dimension).
- ◇ Count accumulation display.
- ◇ Precision engineered throughout, coupled with Easy Maintenance and integral, enhanced Self-Test & 'In-the-Field' based Engineering Diagnostic support software.

Specifications

- ◇ Dimensions: 275(L) x 220(w) x 250(h)mm.
- ◇ Weight: 5.3kg.
- ◇ Speeds: 800, 1,100 and 1,500 documents per minute.
- ◇ Capacity: Hopper feed capacity = +450 notes (Condition Dependant).
Stacker tray capacity = 200 notes (125 in continuous count).
- ◇ Documents Range: Thickness: 0.05 – 0.2mm.
Size: 110 x 55mm (Minimum) to 190 x 95mm (Maximum).
- ◇ Voltage: 220Volts/50Hz AC,
- ◇ Approval: 'CE' & 'UL'.

Shipping

- ◇ Individual Carton: 31(L) x 30(w) x 31(h)cm (0.03CBM) at GW of 6.0kg.